



1" Deflection Rated Load (lbs)	Threaded Rod	
E21, E55, E79, E106, E143, E187 ET20, ET42, ET80, ET129, ET194	Ø1/2"	12" LG
E244, E318, E415, E500, E633 ET255, ET347, ET473, ET667	Ø5/8"	14-1/4" LG
E806, E1030, E1230, E1490	Ø3/4"	
E1810, E2210, E2705	Ø7/8"	

2" Deflection Rated Load (lbs)	Threaded Rod	
F33, F43, F59, F83, F120, F155, F195 FT30, FT41, FT60, FT85, FT121	Ø 1/2"	12" LG
F348, F453, F497, F590, F676 FT171, FT241	Ø 5/8"	16-1/4" LG
F781, F787, F825, F918, F978, F1000	Ø 3/4"	
F1159, F1408, F1710, 2149, F2700	Ø 7/8"	

**Notes:**

Dimensions in inches  
Loads in pounds.

**Surface Treatments**

Hardware Zinc Plated.  
Hat and pressure plate Black Primer.  
Springs Powder coated or Zinc Plated.

\* Hat dimensions are dependant on spring selection. Check with Caldyn.

**Springs**

ET and FT springs are tilt springs.

3" Deflection Rated Load (lbs)	Threaded Rod	4" Deflection Rated Load (lbs)	Threaded Rod
G213, G303	Ø 5/8" 20" LG	H154, H221	Ø 5/8" 20" LG
G853	Ø 3/4" 23" LG	H624, H883	Ø 3/4" 23" LG
G1223	Ø 7/8"	H1294, H1553	Ø 7/8"



CALIFORNIA DYNAMICS CORPORATION  
5572 ALHAMBRA AVE. LOS ANGELES CA, 90032  
PH 323-223-3882 FAX 323-223-7941

email: caldyn@earthlink.net

"CALL US - TO SET THINGS RIGHT"

Assoc. Member



JOB:

CUSTOMER:

TAG:

Dwg. No.

F345

PREP By:

CHKD By:

DO NOT SCALE DRAWING

Date

02/07/14

Date

Date

TYPE

**PRI**

PIPE RISER  
PRE-LOADED  
1", 2", 3" and 4"  
DEFLECTION