



TYPICAL CALLOUT
 Mount Type **RQD B 200**
 Size Color

MAXIMUM LOAD RATINGS (lbs)

COLOR CODE	SIZE		
	A	B	C
ORANGE	40	120	—
YELLOW	55	200	300
GREEN	80	280	520
BLUE	130	400	750
WHITE	—	—	1100

Mount Locations



Mount Locations	Mount Selections

Notes:

Dimensions are in inches.

Type RQ: Single Deflection ($\frac{1}{4}$ " Max.)

Type RQD: Double Deflection ($\frac{1}{2}$ " Max.)

Neoprene Type	DIMENSION (Inches)							
	A	B	C	D	L	J	W	H
RQ - A	3.50	2.00	1.00	.44	4.50	1.00	3/8	2.50
RQ - B	4.31	2.50	1.25	.56	5.38	1.50	5/8	2.75
RQ - C	5.00	3.25	1.625	.69	6.19	1.88	3/4	3.38
RQD - A	3.50	2.00	1.00	.44	4.50	1.00	3/8	2.50
RQD - B	4.31	2.50	1.05	.56	5.38	1.50	5/8	3.38
RQD - C	5.00	3.25	1.625	.69	6.19	1.88	3/4	4.48



CALIFORNIA DYNAMICS CORPORATION
 5572 ALHAMBRA AVE. LOS ANGELES CA, 90032
 PH. 323-223-3882 FAX. 323-223-7941
 email: caldyn@earthlink.net

"CALL US - TO SET THINGS RIGHT"

Assoc. Member



JOB: _____
 CUSTOMER: _____
 TAG: _____

Dwg. No. **F457** Date **7/11/16**
 PREP By: _____ Date _____
 CHKD By: _____ Date _____
 DO NOT SCALE DRAWING

TYPE
RQ & RQD
 NEOPRENE MOUNT
 WITH INTEGRAL
 SEISMIC RESTRAINTS