



+The ratio of the spring diameter to it's height at rated deflection is not under .8 and extra deflection is not less than 50%.

Operation Height may equal Free Height depending upon load and adjustment.

ID numbers are multi-purpose. They identify the products as well as the deflection rating in inches and load ration in pounds. For example: E415 indicates 1 inch deflection rating and 415 pounds load rating for the SSK 415.

For compact support of heavy loads many SSK's include inner springs. For low profile support of heavy loads, many SSK's have clustered springs.

Installation Instructions See file F33

Isolator Locations	_

Isolator Locations	Isolator Selections

3 Inch Deflection Rating								
ID Numbers	W	S	F	Х	RD	Free HT.		
G213, G303	3	6	4-1/2	3	1/2NC	8-1/4		
G426, G606	3	10	8-1/2	7	5/8NC			
G853, G1223	4	7	5-1/2	4	J/OINC	9-1/4		
G1706, G2446	4	12	10-1/2	9	3/4NC	9-3/8		
G3412, G4892	8	11	9-1/2	8	7/8NC	9-7/8		
G5971, G7677	12	15	13-1/2	40.4/0	3-1/2 12	1-NC	10	
G11007	12	15	13-1/2	12	1-140	10-1/4		

1 Inch Deflection Rating						
ID Numbers	W	s	F	Х	RD	Free HT.
E21, E55, E79, E106 E143, E187, E244, E318, E415	2	5	3-1/2	2	3/8NC	4-1/4
ET473, ET667		_	- 4/0		1/2NC	4-1/2
ET940,ET1326, E1660 E2000, E2532, E3204	4	7	5-1/2	4	5/8NC	5-1/8
E3735, E4500, E5697, E7209	6	9	7-1/2	6	3/4NC	5-1/2

2 Inch Deflection Rating						
ID Numbers	W	S	F	Х	RD	Free HT.
FT30, FT41, FT60, FT85 FT121	3	6	4-1/2	2-1/2		5-1/2
FT171,FT241,F348,F453 F590, F676, F787, F918		0	4-1/2	3	1/2NC	6-1/2
F1159, F1408, F1710	4	7	5-1/2	4	5/8NC	8-1/8
F2360, F2704, F3148, F3672	6	9	7-1/2	6	3/4NC	7
F4077, F5310, F6084, F7083, F8262	9	12	10-1/2	9	7/8NC	7-1/2

	4 Inch Deflection Rating						
	ID Numbers	W	Ø	F	Χ	RD	Free HT.
l	H154, H221	4	7	5-1/2	4	1/2NC	8-7/8
	H308, H442	t	11	9-1/2	8	1/2110	0-170
	H624, H883	5	8	6-1/2	5	5/8NC	11
	H1248, H1766	ວ	14	12-1/2	11	3/4NC	11-1/4
	H2496, H3532	10	13	11-1/2	10	7/8NC	11-1/2
	H4368, H5616	14	17	15-1/2	14	1-NC	11-3/4
	H7947	15	18	16-1/2	15	1-1/8NC	12

|--|

CALIFORNIA DYNAMICS CORPORATION 5572 ALHAMBRA AVE. LOS ANGELES CA, 90032 PH. 323-223-3882 FAX. 323-223-7941

email: caldyn@earthlink.net

"CALL US - TO SET THINGS RIGHT

Assoc. Member

CUSTOMER:		

JOB:

TAG:

	Dwg. No. <b>F551</b>	Date 9/20/16	TYPE
-	PREP By:	Date	
-	CHKD By:	Date	SF

DO NOT SCALE DRAWING

SSK

SPRING ISOLATOR BARE, UNHOUSED