



Isolator Location



SEISMIC RESTRAINT RATING	
TBD	UP
TBD	END
TBD	SIDE

TYPICAL CALLOUT	
RJEHD	- 5880
(Type)	- (Load lbs)

Notes:

Steel compression springs isolate loads up to 5880 LBS per mount. Moderate spring deflections generally result in usage under medium through high speed equipment such as generator sets, pumps, air conditioning compressors, transformers, boilers, chillers, etc...

Isolator Selection	Isolator Location

ISOLATOR CHARACTERISTICS			
Max. Load (lbs)	Max. Defl. (in)	Spring Rate (lbs/in)	Quantity Springs
5880	.78	7569	3



CALIFORNIA DYNAMICS CORPORATION
 20500 PRAIRIE ST. CHATSWORTH CA, 91311
 Phone 323-223-3882
 Email: caldyn@caldyn.com

"CALL US - TO SET THINGS RIGHT"

JOB: _____
 CUSTOMER: _____
 TAG: _____

Dwg. No. F300	Date
PREP By:	Date
CHKD By:	Date
DO NOT SCALE DRAWING	

TYPE
RJEHD
 ISOLATOR/RESTRAINT
 EXTRA HEAVY DUTY
 PERFORMANCE
 RATED