



TYPICAL CALLOUT	
Pipe Riser	Spring Size
PRI - ET473	

Notes:

Dimensions in inches
Loads in pounds.

Surface Treatments

Hardware Zinc Plated.
Hat and pressure plate Black Primer.
Springs Powder coated or Zinc Plated.

* Hat dimensions are dependant on spring selection. Check with Caldyn.

Springs

ET and FT springs are tilt springs.

1" Deflection Rated Load (lbs)	Threaded Rod	
E21, E55, E79, E106, E143, E187 ET20, ET42, ET80, ET129, ET194	Ø1/2"	12" LG
E244, E318, E415, E500, E633 ET255, ET347, ET473, ET667	Ø5/8"	14-1/4" LG
E806, E1030, E1230, E1490	Ø3/4"	
E1810, E2210, E2705	Ø7/8"	

2" Deflection Rated Load (lbs)	Threaded Rod	
F33, F43, F59, F83, F120, F155, F195 FT30, FT41, FT60, FT85, FT121	Ø 1/2"	12" LG
F348, F453, F497, F590, F676 FT171, FT241	Ø 5/8"	16-1/4" LG
F781, F787, F825, F918, F978, F1000	Ø 3/4"	
F1159, F1408, F1710, 2149, F2700	Ø 7/8"	

3" Deflection Rated Load (lbs)	Threaded Rod	
G213, G303	Ø 5/8"	20" LG
G853	Ø 3/4"	23" LG
G1223	Ø 7/8"	

4" Deflection Rated Load (lbs)	Threaded Rod	
H154, H221	Ø 5/8"	20" LG
H624, H883	Ø 3/4"	23" LG
H1294, H1553	Ø 7/8"	



CALIFORNIA DYNAMICS CORPORATION
20500 PRAIRIE ST. CHATSWORTH CA, 91311
Phone 323-223-3882
Email: caldyn@caldyn.com

"CALL US - TO SET THINGS RIGHT"

JOB: _____
CUSTOMER: _____
TAG: _____

Dwg. No. F345	Date 12/21/16
PREP By:	Date
CHKD By:	Date
DO NOT SCALE DRAWING	

TYPE
PRI
PIPE RISER
PRE-LOADED
1", 2", 3" and 4"
DEFLECTION